

The foundations of machine learning and deep learning

by **Mohamed Yosef**
mohamedyosef101@outlook.com

First published: 14th of April 2024
Last updated: 13th of December 2024

Abstract

This paper explores the foundational concepts of machine learning (ML) and deep learning (DL), providing both a detailed understanding for both researchers and beginners aiming to develop a solid grasp of when and how to use different models effectively. It delves into essential techniques for improving model performance, including regularization and hyperparameter tuning and highlights core components of deep learning such as activation functions, loss functions, and optimizers, while focusing on foundational methods that remain impactful today. CNNs, RNNs, and Transformers are briefly discussed, along with an in-depth examination of model evaluation metrics and the full model life cycle. The papers aims to provide a comprehensive guide for choosing, tuning, and improving ML and DL models across various applications.

Contents


1	Foundations of Machine Learning	1
1.1	ML Paradigms	2
1.2	Generalization	4
1.3	Choosing the right model	5
2	Deep Learning	6
2.1	Activation Functions	6
2.2	Loss	7
2.3	Optimization	9
2.4	Model life cycle	10
2.5	Architectures	11

Introduction

Machine learning (ML) and deep learning (DL) have rapidly transformed from academic papers to real applications driving innovation across industries. From powering recommendation systems and personal assistants to enabling breakthroughs in healthcare, ML and DL have proven their ability to solve complex problems in ways traditional methods cannot. Despite the vast advancements in both fields, the foundational concepts are valuable for building robust, efficient, and interpretable models.

The importance of understanding these foundations cannot be overstated. Whether you're a beginner or an experienced researcher, grasping the underlying mechanisms of ML and DL models is essential for choosing the right model for a given task, optimising its performance, and ensuring it remains interpretable. In an era where models are often seen as black boxes, this knowledge provides the clarity needed to trust and refine AI systems.

The purpose of this paper is to equip readers with a comprehensive guide to the core principles of machine learning and deep learning. Beyond just understanding the basics, this paper aims to provide the necessary insights to choose, apply, and improve models across various scenarios. By building a solid foundation, readers will be empowered to make informed decisions in developing and enhancing their models, ultimately driving better outcomes in their respective fields.



1 Foundations of Machine Learning

Since machine learning uses data to actually learn, the most efficient way to use data is a matrix. Let's call our matrix $X \in \mathbb{R}^{m \times n}$ (shown in Figure 1), where n is the number of data points, and m is the number of features. A **feature** is a property of the data point represented in a column. Each row of the data matrix X is an example data point, $x \in \mathbb{R}^m$. You can think of each row as a vector, and each entry of the vector represents the value of the data point for a particular feature.




Figure 1: A matrix of house pricing data with some made-up numbers where the features are number of rooms, house size, city, and price. Each row/vector represents a house or a data point while each value in a row called entry.

In machine learning, we consider each data point (row) as an example that the model (the AI) learns from. Let's say I have a friend called Ahmed who wants to be a physician but instead of learning from textbooks and medical school, he decided to learn from patients and see each patient as an example (he just observes now). After observing a good number of patients, Ahmed now has some general rules of how to deal with new patients, and this generalization thing is the core idea behind machine learning.

So, the machine learns by first getting some data points structured in a matrix. After that, you need to manually extract useful features from the data then pass these data points into the model and finally you will get the result (like explained in Figure 2). But the game has not ended yet, you may want to get higher result by getting more data, try other features, or even try another model. I know that this is too much, so what about focusing in this simple question: how to do machine learning? Well, there are three main types of machine learning you need to know...



Figure 2: Machines learn from examples by extracting useful features manually or automatically (like in deep learning) then pass these features into a model to get the result.

1.1 ML Paradigms

There are three main paradigms in machine learning: supervised, unsupervised, and reinforcement learning. Supervised learning is the most common one in AI. In supervised learning, we are not only given a matrix of data X , but each data point x_i also has an associated label, y_i that we want to predict. Inside supervised learning, there are two categories; (1) **regression** where you predict a continuous variable like predicting how much oxygen a COVID-19 patient needs up to four days in advance to help hospitals allocate resources for those in need (Sriram et al., 2021). And (2) **classification** where you assign objects or data points to predefined categories or classes like detecting skin cancer in the early stages (Mahmoud and Soliman, 2024).




Figure 3: Data from the iris dataset proposed by (Fisher, 1936). The x and y axes are two of the features. The left figure shows the true labels for each of the data points, where red points belong to the setosa class, pink are virginica, and green are versicolor. The right figure shows an assignment of each point to a cluster, learned via k-means clustering (Sanchez, 2020).

In **unsupervised learning**, we no longer have labels Y . Instead, we pass the data points of the matrix X into the model, hoping that the model can find the pattern in the data. Unsupervised learning techniques give us the ability to explore the structure or the distribution of the data (Raschka, 2022). A well-known

clustering algorithm is k-means clustering (MacQueen, 1967), which learns to assign each data point to one of k clusters such that the distance between all points within the same cluster is minimized. Formally, it partitions the n observations into k sets $S = \{S_1, S_2, \dots, S_k\}$ to minimize the difference between points and the mean of the points in the cluster:

$$\arg \min_s \sum_{i=1}^k \sum_{x \in S_i} \|x - \mu_i\|^2$$

where μ_i is the mean of the points in cluster S_i . Figure 3 (right) shows an example of k-means clustering applied to the iris data. In this example, with only two features and no access to the true labels, k-means is not able to learn a partitioning of the data into clusters that matches the true labels.

Another subfield of unsupervised learning is **dimensionality reduction**. Most of the times, it is helpful to work with fewer features (i.e dimensions) and still retaining the meaningful properties of the data, which in turn requires less storage space (Raschka, 2022). Additionally, the learning algorithm can run much faster and achieve better performance as we reduce the number of irrelevant features (or noise).

Not all ML problems fall into the supervised/unsupervised division. If you think about how we (as humans) learn and the nature of learning, you will clearly see that you learn by interacting with your world (or environment). At the same time, you are acutely aware of how your world responds to what you do, and your goal is to get the best results through your actions. The same thing happens with our little agent; the agent learns from the world/environment by interacting with it, through trial and error, and receiving rewards; negative or positive as feedback for performing actions. The agent is not told which actions to take at first, but the agent uses the feedback from the environment to discover which actions yield the most reward.




Figure 4: Reinforcement learning process starts with the agent observing the state of the environment and take action according to the agent’s policy then receives a reward negative or positive from the environment and move to the next state after that the process repeats. Based on a similar figure in (Sutton and Barto, 2018).

Reinforcement learning differs from supervised learning; supervised learning is learning from a training set of labelled examples provided by a knowledgeable external supervisor giving the AI the solution and the right action to take in a specific situation. The goal of supervised learning is to generalize a rule for the AI to deal with other situations that are not in the training set. But in real-world interactive problems, the answer often emerges through exploration and trial and error. There might not be a definitive “correct” answer for every situation the agent encounters. Even if there is a right answer for some situations,

it will not work well as a general solution (Sutton and Barto, 2018).

Reinforcement learning is also different from unsupervised learning; unsupervised learning is finding structure hidden in the collection of unlabelled data. Understanding the hidden structure can be useful in reinforcement learning, but unsupervised learning itself does not maximize the reward signal.

So, reinforcement learning is the third machine learning paradigm alongside supervised learning and unsupervised learning with a goal to maximize the total rewards that the agent gets from the environment.

1.2 Generalization

One of the big challenges in machine learning is to improve generalization, which is the ability to put general rules from seen data to deal with new, unseen data. Basically, we split our data into three subsets: the training, validation, and test sets. Knowing the difference between the training error and the validation error can help us identify two common phenomena: underfitting and overfitting. Underfitting occurs when a model cannot learn from the training data. When the model is able to perfectly predict the training data, it might begin to overfit the data, i.e. the model knows more than enough so it fails to generalize.




Figure 5: A classification task where the model must separate class 1 (green X's) from class 2 (circles). Three decision boundaries are shown in red. Underfitting occurs when the model capacity is not sufficient to accurately partition the data (a). Here, a linear decision boundary is too simple for the curved distribution of the class labels. However, if the model capacity is too great, it may overfit the data, perfectly capturing the idiosyncrasies of the training data at the expense of generalization error (c) (Nautiyal, 2017).

Another idea that is related to overfitting and underfitting is **bias-variance tradeoff**. Firstly, **bias error** happens when the learning algorithm makes incorrect assumptions; e.g. assuming the data is linearly separable when it is curved which leads to underfitting and therefore high error. Secondly, **variance** says how much your results will change if you train the model on a slightly different dataset.

The **bias-variance tradeoff** is an important idea that relates to overfitting and underfitting. **Bias error** is a result of incorrect assumptions made by the learning algorithm; for example, assuming the true decision boundary is linear when it is actually curved. High bias can lead to underfitting and therefore high training or approximation error. **Variance** ($Var(\hat{w})$) describes how much the solution found by the learning algorithm is sensitive to small fluctuations in the training data. If the model has a high variance, we

expect that the solution may change significantly if we re-sample a new dataset. High variance can lead to overfitting, where the model learns the quirks and noise in the training data too well, but fails to generalize well to unseen data. There are ways to deal with overfitting; like regularization or maybe increasing the training size in some cases, but I'll introduce these techniques in section 2.2.

1.3 Choosing the right model

Choosing the right machine learning model depends on various factors like the type of data, the problem you're solving, and the balance between accuracy, interpretability, and resource needs. It's not just about picking the most advanced model but selecting the one that fits your specific context.

First, look at your data. If you have a small dataset, simpler models like linear regression or decision trees are often better as they don't overfit easily. With larger datasets, complex models like random forests or deep learning can uncover deeper patterns. The type of features you have also matters—categorical data may suit decision trees, while continuous data can benefit from linear regression or support vector machines. In high-dimensional settings, where you have more features than data points, techniques like regularization or dimensionality reduction help manage complexity before applying models like neural networks.

The nature of the problem—whether it's classification, regression, or clustering—will guide your model choice too. For classification tasks like detecting spam, models like logistic regression or decision trees are common. If you're tackling something more intricate, like image recognition, convolutional neural networks (CNNs) can handle spatial data better. In regression, when predicting continuous values, linear models work well for straightforward tasks, but for non-linear ones, models like random forests or support vector regression excel. When you need to group data points (as in customer segmentation), clustering methods like k-means or DBSCAN are useful, depending on whether you need to handle noise or predefined clusters.

Finally, there's a trade-off between interpretability and performance. Simpler models like logistic regression are easy to understand but might not capture complex relationships in the data. On the other hand, high-performing models like deep learning offer more accuracy but are harder to interpret. Computational resources are another key factor—if you're working with limited resources, simpler models are often more practical. However, when you have the power to train more complex models, they can yield higher performance, though at the cost of increased computational time and complexity.

2 Deep Learning

Deep learning drives many applications and services, including digital assistants, voice-enabled TV remotes, credit card fraud detection, self-driving cars, and generative AI. Unlike traditional machine learning, deep learning can handle unstructured data, such as text and images, without extensive preprocessing, also deep learning algorithms automate feature extraction, which reduces dependency on human expertise. As shown in Figure 6, the core of deep learning is a neural network that is made up of layers (input, hidden, and output) that contain nodes. Each node computes its output based on a set of weights (or parameters) applied to the output of the previous layer.




Figure 6: A simple neural network with two hidden layers (in red), and a one-dimensional output layer (designed with NN-SVG. <https://alexlenail.me/NN-SVG>).

The layer in Figure 6 is the input layer which applies the inputs from data x . To compute the output of all the nodes within a layer (say the first hidden), we use matrix multiplication: $h^{(1)} = \sigma(W^{(1)}x)$, where $W^{(1)}$ is the matrix of weights (or parameters) for the first hidden layer, while σ is the activation function.

2.1 Activation Functions

An **activation function** is a fancy way of saying that we are making the output of each neuron non linear because we want to learn non-linear relationships between the input and the output. Without a non-linear activation function, even the deepest network is as good as a single one. There are 3 types of ac-

tivation functions: binary step function, linear function, and — the most important one — non-linear functions.

Binary step function depends on a threshold value that decides whether a neuron should be activated or not. Basically, we compare the inputs with a certain threshold; if the input is greater than it, then the neuron is activated, else it is deactivated, meaning that its output is not passed on to the next hidden layer.

Linear activation function is another type of activation functions where the activation is proportional to the input. The function doesn't do anything to the weighted sum of the input, it simply outputs the value it was given.




Figure 7: (a) Binary step activation function when the inputs is greater than or equal to zero, it is activated, else it is deactivated. (b) simple linear activation function follow the equation $x = y$ at any point in real numbers.

2.2 Loss

If you think for a moment, you will find out that step functions and linear functions are difficult to optimize and can not solve a lot of problems. Therefore, **non-linear activation functions** come as a magical way to solve any complex problem, especially the non-linear ones. Common activation functions are logistic sigmoid, Tanh, and rectified linear unit (ReLU). You can see in Figure 2.3 that **logistic sigmoid** outputs a value between 0 and 1, but suffers from vanishing gradients during training. While **Tanh** is similar to sigmoid but outputs values between -1 and 1. A more frequently used activation function is **ReLU (Rectified Linear Unit)** which is simple and efficient, outputs the input directly if positive, otherwise outputs zero. There are variants of ReLU; like Leaky ReLU that address the “dying ReLU” problem (Xu et al., 2015).

Let's go back to supervised learning to understand some important concepts, such as loss and optimization. As a reminder, in supervised learning, we want to predict the label y given a data point x . Therefore, we make a prediction $\hat{y} = f(x)$. But how can we learn useful information from our prediction? First, we need to define our model and I'm going to use simple **linear regression** as an example:




Figure 8: Non-linear activation function like logistic sigmoid, Tanh, and ReLU.

$$\hat{y} = w^T x$$

Here, w is a vector containing the weights/parameters of the network and this weight is how much a feature i affects the outcome of the model (e.g. the size of the house may affect the price while the color of the doors may not). So, to measure how good or bad our predictions are, we use a loss function. Common loss functions include **Mean Squared Error (MSE)** which squares the difference between predicted and actual values. Also, we have **Cross-Entropy Loss** which is mostly used for classification problems and measures the probability distribution difference between predictions and true labels. With our linear regression model, I'm going to use the mean squared error loss function:

$$\hat{L}(X, y) = 1/n \sum_{i=1}^n (\hat{y}_i - y_i)^2$$

We can now minimize this loss by finding the point at which the gradient of the loss with respect to the weights (or parameters) w is zero (i.e., $\nabla_w \hat{L} = 0$). Thus, we can determine the optimal weight vector: $w = (X^T X)^{-1} X^T y^T$ (Goodfellow et al., 2016).

In section 1.2, I talked about overfitting and underfitting without presenting a way to fix the problem. Here we'll use **regularization** as a way to deal with bias-variance tradeoff and hopefully get a better model for generalization. It achieves this by adding a **penalty term** to the loss function, discouraging the model from assigning too much importance to individual features or coefficients. One of the common examples of regularization is **weight decay**, which introduces a penalty on the norm of the weights, e.g.:

$$J(w) = \hat{L}(X, y; w) + \lambda w^T w$$

where the **hyperparameter** λ controls the strength of the penalty. I want you to know that all deep learning algorithms have hyperparameters that must be tuned by testing the model performance.

2.3 Optimization

In any machine learning and deep learning model, we want to minimize the loss function by updating the parameters iteratively during training. In traditional machine learning, we can easily optimize the loss and reach the optimal point — the point with the least value of loss — but due to the number of parameters in neural networks, finding the global minimum becomes difficult.




Figure 9: Red areas show regions of parameter space where the loss is high, blue areas show regions where the loss is low. Convex loss functions (a) can be found in traditional machine learning models and are easily to optimize, while neural network architectures can lead to complicated loss landscapes (b). Reproduced by (Jaques, 2019) from (Li et al., 2017)

So, to find a good optimizer, we need a more complicated technique like **gradient-based optimization** which finds the minimum by dividing the loss landscape into steps with size α or learning rate. A most basic gradient algorithm is **stochastic gradient descent (SGD)** where at each step, SGD randomly samples a batch of training data (a smaller group of the dataset) and computes the gradient loss with respect to the model parameters $\nabla_w \hat{L}(X_B; w)$. The parameters are then updated by moving in the direction of the steepest descent (opposite to the gradient).

The computational cost of SGD is linear in the size of the batch. Using a smaller batch requires less computation and memory, but introduces more noise to the gradient updates (Dinh, 2018). Beyond SGD, techniques like Adam (Kingma and Ba, 2017), RMSProp, and Adagrad help escape local minima and converge faster by adaptively adjusting learning rates and computing a moving average of the gradient estimates as a form of **momentum** (Nesterov, 2013, Sutskever et al., 2013).

2.4 Model life cycle

Model building projects (shown in Figure 10) follow a well-established life cycle. The first step involves creating a baseline model, a simple initial version that serves as a foundation for further development. Next, you feed your data into the model, which trains it to learn the underlying patterns and relationships. This training process is followed by rigorous testing to evaluate the model's performance. During testing, you can identify issues like overfitting, where the model memorizes the training data too closely and performs poorly on unseen data, or underfitting, where the model fails to capture the complexities of the data and has low accuracy. Based on the results of this evaluation, you can diagnose these issues and make adjustments to improve the model's performance. This might involve trying different algorithms, tweaking parameters, or gathering more data. You then train the improved model again and repeat the entire process until it meets your desired level of accuracy and generalizability.




Figure 10: Model building follows a cycle: create a baseline model, train, test, diagnose the issues like overfitting and underfitting, improve, train it again, and repeat this process until it meets your performance goals.

How to diagnose what's happening in your model? The first thing that you need to know is that it's good to have one main metric to evaluate your model, like the MSE that we used before. Other evaluation metrics like **accuracy** which is the proportion of correct predictions for a classification task. We also have **Precision and Recall** (shown in figure 2.6) are used to measure the ability of the model to identify true positives and avoid false positives/negatives (relevant for imbalanced datasets). Sometimes you want to free your head and use **F1-Score** which is the harmonic mean of precision and recall.

2.5 Architectures

Until now, we only talked about one type of neural networks which is a fully-connected network or feed-forward neural network. In an image classification problem like MNIST (Lecun et al., 1998) where we have only 28 by 28 pixels which means 784 neurons in the input layer, but what if we have a bigger image say 100 by 100 pixels, this will make our hidden layer contains 10 000 neurons and if we have one hidden layer with 100 neurons, it will need one million parameters which is a huge number of parameters to train for just an image. So, to be more flexible, we can use partially connected layers like in convolutional neural networks (CNNs) (Lecun et al., 1998);(Fukushima, 1980). These networks contain learned **filters** that are applied across all parts of the input, which is typically an image. In this way, the networks can learn functions which are **translation invariant**. For example, the network can learn a filter to detect a cat, and because it will be applied across many positions in the input image, the network can detect cats in any part of the image.




Figure 11: A brief illustration of a ventral stream of the visual cortex in the human vision system. It consists of primary visual cortex (V1), visual areas (V2 and V4) and inferior temporal gyrus (Wang and Raj, 2017).

Another type of architecture is **recurrent neural networks** (RNNs) which model **sequential data**, meaning they have **sequential memory**. An RNN takes in different kinds of inputs (text, words, letters, parts of an image, sounds, etc.) and returns different kinds of outputs (the next word/letter in the sequence, paired with a fully-connected network it can return a classification, etc.). While this can give an RNN a rudimentary form of **memory**, it also exacerbates problems with **vanishing and exploding gradients**. Because computing the gradient depends on multiplying by the same parameter values repeatedly, this can cause the gradients to explode (if the parameter is greater than one) or vanish (if the parameter is less than one). **Long Short-Term Memory** (LSTM) networks (Hochreiter and Schmidhuber, 1997) help to address this problem by adding an **input, output, and forget gate** to each recurrent cell. These gates allow the network to learn when to update the information in the cell and when to erase it, rather than simply multiplying by the same parameters each time.




Figure 12: A recurrent neural network with one hidden unit (left) and its unrolling version in time (right). The unrolling version illustrates what happens in time: s_{t-1} , s_t , and s_{t+1} are the same unit with different states at different time steps. (LeCun et al., 2015)

Recently, **transformers** have emerged as an alternative to RNNs (Vaswani et al., 2017). These models make use of an **attention** mechanism to summarize inputs of varying lengths based on dynamically changing, learned attention weights. Transformers have been shown to be highly effective at modelling sequences of data, and consequently have led to impressive results in music generation (Huang et al., 2018) and text generation (Radford et al., 2019).

Final Words

I tried to get you through the foundation of machine learning and deep learning, but there are many concepts to learn and many applications to try. For this reason, you may like to take a look at the following resources: (Ying, 2022) for an overview of traditional ML algorithms, (Raschka, 2022) for more details and code examples, (Turp, 2023) for an overview of deep learning, (Sanderson, 2017) for visualizing the deep learning concepts, and (Zhang et al., 2021) for more details and code examples.

تم بحمد الله

References

- Laurent Dinh. Reparametrization in deep learning. *Papyrus*, October 2018. URL <https://papyrus.bib.umontreal.ca/xmlui/handle/1866/21139>.
- Ronald Fisher. The use of multiple measurements in taxonomic problems. *Annals of Eugenics*, 7(2): 179–188, September 1936. ISSN 2050-1420, 2050-1439. doi: 10.1111/j.1469-1809.1936.tb02137.x. URL <https://onlinelibrary.wiley.com/doi/10.1111/j.1469-1809.1936.tb02137.x>.
- Kunihiko Fukushima. Neocognitron: A self-organizing neural network model for a mechanism of pattern recognition unaffected by shift in position. *Biological Cybernetics*, 36(4):193–202, April 1980. ISSN 1432-0770. doi: 10.1007/BF00344251. URL <https://doi.org/10.1007/BF00344251>.
- Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep learning*. MIT Press, 2016. ISBN 978-0-262-03561-3. URL <https://mitpress.mit.edu/9780262035613/deep-learning/>.
- Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural Computation*, 9(8):1735–1780, November 1997. ISSN 0899-7667, 1530-888X. doi: 10.1162/neco.1997.9.8.1735. URL <https://direct.mit.edu/neco/article/9/8/1735-1780/6109>.
- Cheng-Zhi Anna Huang, Ashish Vaswani, Jakob Uszkoreit, Noam Shazeer, Ian Simon, Curtis Hawthorne, Andrew M. Dai, Matthew D. Hoffman, Monica Dinculescu, and Douglas Eck. Music transformer, 2018. URL <https://arxiv.org/abs/1809.04281>.
- Natasha Jaques. *Social and affective machine learning*. PhD dissertation, Massachusetts Institute of Technology, 2019. URL <https://www.media.mit.edu/publications/social-and-affective-machine-learning/>.
- Diederik P. Kingma and Jimmy Ba. Adam: a method for stochastic optimization, January 2017. URL <http://arxiv.org/abs/1412.6980>.
- Y. Lecun, L. Bottou, Y. Bengio, and P. Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, November 1998. ISSN 1558-2256. doi: 10.1109/5.726791. URL <https://ieeexplore.ieee.org/document/726791>.
- Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *Nature*, 521(7553):436–444, May 2015. ISSN 1476-4687. doi: 10.1038/nature14539. URL <https://www.nature.com/articles/nature14539>.
- Hao Li, Zheng Xu, Gavin Taylor, Christoph Studer, and Tom Goldstein. Visualizing the loss landscape of neural nets. *ArXiv*, November 2017. doi: 10.48550/ARXIV.1712.09913. URL <https://arxiv.org/abs/1712.09913>.
- J. MacQueen. Some methods for classification and analysis of multivariate observations. In *Proceedings of the fifth Berkeley symposium on mathematical statistics and probability*, pages 281–297, 1967. URL <https://api.semanticscholar.org/CorpusID:6278891>.
- Nourelhoda M. Mahmoud and Ahmed M. Soliman. Early automated detection system for skin cancer diagnosis using artificial intelligent techniques. *Scientific Reports*, 14, April 2024. ISSN 2045-2322. doi: 10.1038/s41598-024-59783-0. URL <https://www.nature.com/articles/s41598-024-59783-0>.
- Dewang Nautiyal. Underfitting and overfitting, November 2017. URL <https://www.geeksforgeeks.org/underfitting-and-overfitting-in-machine-learning/>.

- Yu. Nesterov. Gradient methods for minimizing composite functions. *Mathematical Programming*, 140 (1):125–161, August 2013. ISSN 1436-4646. doi: 10.1007/s10107-012-0629-5. URL <https://doi.org/10.1007/s10107-012-0629-5>.
- Alec Radford, Jeff Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language models are unsupervised multitask learners, 2019. URL <https://api.semanticscholar.org/CorpusID:160025533>.
- Sebastian Raschka. *Machine Learning with PyTorch and Scikit-Learn*. Packt Publishing Limited, feb 2022. ISBN 978-1-80181-931-2 978-1-80181-638-0.
- Belen Sanchez. Predicting iris flower species with k-means clustering in python. *Medium*, January 2020. URL <https://medium.com/@belen.sanchez27/predicting-iris-flower-species-with-k-means-clustering-in-python-f6e46806aaee>.
- Grant Sanderson. What is a neural network, October 2017. URL <https://youtu.be/aircAruvnKk?si=91jMWClvdSSXcDxL>.
- Anuroop Sriram, Matthew J. Muckley, Koustuv Sinha, Farah Shamout, Joelle Pineau, Krzysztof J. Geras, Lea Azour, Yindalon Aphinyanaphongs, Nafissa Yakubova, and William Moore. COVID-19 prognosis via self-supervised representation learning and multi-image prediction. *CoRR*, abs/2101.04909, 2021. URL <https://arxiv.org/abs/2101.04909>.
- Ilya Sutskever, James Martens, George Dahl, and Geoffrey Hinton. On the importance of initialization and momentum in deep learning. In *Proceedings of the 30th International Conference on Machine Learning*, pages 1139–1147. PMLR, May 2013. URL <https://proceedings.mlr.press/v28/sutskever13.html>.
- Richard Sutton and Andrew Barto. *Reinforcement Learning: An Introduction*. MIT Press, second edition edition, November 2018. ISBN 978-0-262-03924-6. URL <https://mitpress.mit.edu/9780262039246/reinforcement-learning/>.
- Misra Turp. 50 days of deep learning, 2023. URL <https://www.youtube.com/playlist?list=PLM8IYG2MzHmQn55ii0duXdO9QSoDF5myF>.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention Is All You Need, 2017. URL <http://arxiv.org/abs/1706.03762>.
- Haohan Wang and Bhiksha Raj. On the origin of deep learning, 2017. URL <https://arxiv.org/abs/1702.07800>.
- Bing Xu, Naiyan Wang, Tianqi Chen, and Mu Li. Empirical evaluation of rectified activations in convolutional network. *ArXiv*, 2015. doi: 10.48550/ARXIV.1505.00853. URL <https://arxiv.org/abs/1505.00853>.
- Kylie Ying. Machine learning for everyone, 2022. URL https://youtu.be/i_LwzRVP7bg?si=KeY5CgAfQhAdtOGV.
- Aston Zhang, Zachary Lipton, Mu Li, and Alexander Smola. *Dive into Deep Learning*. D2L, 2021. URL <https://d2l.ai/>.